



WEAR PROTECTION

The hydraulic pump is the heart of your hydraulic system. Any wear can reduce efficiency and system service life. The Shell Tellus® range of hydraulic fluids offers a range of options, including the latest synthetic, ashless technology that can help to extend pump life, even under the most severe conditions, and is cost-effective with zinc-based additive technology for general use.

OIL LIFE

The longer the oil life, the less fluid maintenance is required to help your equipment operate for longer without interruption. The Shell Tellus® range of hydraulic fluids enables you to match the oil life of the fluid to your operational needs. It includes extra-long-life synthetic technologies capable of up to four times standard life¹, and through to cost-effective, reliable products for less demanding applications.



IMPROVED CLEANLINESS

All Shell Tellus® products meet the demanding cleanliness requirements of the DIN industry standard to help provide extra protection, improved filter performance and less maintenance.

SYSTEM EFFICIENCY

To help your equipment perform to its design standards, the hydraulic fluid needs to protect, lubricate and help transmit power in the most effective way possible. Shell Tellus® hydraulic fluids can help maintain or even improve the efficiency of hydraulic systems. From Shell Tellus® S4 ME, which can help improve the energy efficiency of many hydraulic systems, to Shell Tellus® S2 MX and Shell Tellus® S2 VX that provide reliable air release, water separation, filterability, cleanliness and stick-slip performance, there is a choice that can help to optimise your system's efficiency and

costs of operation.

REAL-WORLD VALUE DELIVERY

Shell does not just design fluids for the individual components of a hydraulic system such as the pump, we look at the system more broadly. For instance, Shell Tellus® S4 ME has been designed to benefit the complete system. The result is a fluid that:

- a can help improve the energy efficiency of the system in which
- can help to increase oil life by up to four times compared with conventional oils in the Shell range²
- can help to prolong equipment life through excellent hydraulic pump wear protection

SHELL TELLUS® S4 ME - for the longest oil life in the Shell range



¹Compared with other oils in the Shell range

A RANGE OF HYDRAULIC FLUIDS TO MEET YOUR NEEDS

Shell has designed a portfolio of fluids that enables you to choose a product to match your needs.

THE SHELL TELLUS® "M" RANGE

Industrial, manufacturing and machine use

Shell Tellus® S4 ME

SYNTHETIC

- Extra long life
- Energy saving
- Zinc free



Longer oil life, lower wear and better energy efficiency



Shell Tellus® S3 M

■ Long life

- Industrial applications
- Zinc free



Wider temperature range

Wider

range

temperature

■ Zinc free

- Versatile applications
- Zinc free

24/7

THE SHELL TELLUS® **SPECIALITY RANGE**

Detergent-based fluids for use where water contamination is possible

Shell Tellus® S3 V

THE SHELL TELLUS®

Extended temperature operation

for manufacturing and mobile

Shell Tellus® S4 VX

■ Ultra-low temperature ■ Versatile applications

"V" RANGE

machine use

- Long life



Shell **Tellus® S2** MX

- Extra protection
- Industrial applications
- Long life

444

Better wear protection and longer oil life



Shell Tellus® S2 VX

- Extra protection
- Versatile applications
- Long life



Shell Tellus® S2 VA

- Water tolerant
- Versatile applications





Shell Tellus® S2 MA

- Water tolerant
- Industrial applications



Shell Hydraulic S1 M

- Reliable protection
- Industrial applications

444

APPLICATION ICON KEY

Factory/machine applications



🖺 High load



Ultra-low temperature



Mobile equipment/exterior use



Wet conditions

PRODUCT-NAME SUFFIX KEY

A = Water tolerant

E = Energy saving, high efficiency

M = Manufacturing/machine: factory applications

V = Versatile applications

X = Extra/extreme performance

PRODUCT	BENEFITS	TECHNOLOGY	ISO VISCOSITY GRADES	SPECIFICATIONS AND APPROVALS (Full details of approvals for all products can be obtained from your Shell representative; approvals and claims will vary by viscosity grade.)
Shell Tellus® S4 ME	■ Extra long life ■ Energy saving	Synthetic, ashless	32, 46	Approved by Fives Group, Eaton, Bosch Rexroth and many other equipment manufacturers. Denison approved fluid. Industry standards: ASTM D6158, ISO 11158, DIN 51524-2
Shell Tellus® S3 V	Long life and improved efficiencyVersatile application	Mineral, zinc free	46, 68	Approved by Fives Group, Eaton, Bosch Rexroth and many other equipment manufacturers. Denison approved fluid. Industry standards: ISO 11158, DIN 51524-3, ASTM D6158
Shell Tellus® S3 M	Long life and improved protectionIndustrial applications	Mineral, zinc free	32, 46, 68, 100	Approved by Fives Group, Eaton, Bosch Rexroth and many other equipment manufacturers. Denison approved fluid. Industry standards: ISO 11158, DIN 51524-3, ASTM D6158
Shell Tellus® S2 VX	Extra protectionVersatile applicationLong life	Mineral, zinc-based	HV/15, 22, 32, 46, 68, 100	Approved by Eaton, Fives Group, Bosch Rexroth (RDE 90245) and many other equipment manufacturers. Denison approved fluid. Industry standards: ISO 11158, ASTM D6158 (HV), US Steel 126, DIN 51524-3
Shell Tellus® S2 MX	Extra protectionIndustrial applicationsLong life	Mineral, zinc-based	HM/22, 32, 46, 68, 100	Approved by Bosch Rexroth (RDE 90245), Eaton, Fives Group and many other equipment manufacturers. Denison approved fluid. Industry standards: ISO 11158, ASTM D6158 (HM), US Steel 126, DIN 51524-2
Shell Hydraulic S1 M	Reliable protectionIndustrial applications	Mineral, zinc-based	HM/32, 46, 68	ISO 11158
SPECIALITY GRADES				
Shell Tellus® S4 VX	Ultra-low temperatureVersatile application	Special base oils, ashless	HV/32	Approved by Komatsu Mining, Komatsu and DIETZ automation (servo valve and proportional valve test equipment)
Shell Tellus® S2 VA	Extra protectionWater tolerant	Mineral, zinc- based, detergent	L-HV/46	Industry standards: DIN 51502, ISO 6743/4, ISO 11158, ASTM 6158-05
Shell Tellus® S2 MA	Extra protectionWater tolerant	Mineral, ashless, detergent	46	Approved by Mueller Weingarten (ISO 46) Industry standards: ISO 11158, ASTM 6158-05
Shell Irus® C	Water-glycol based fire-resistant fluid			Contact your Shell representative for details
Shell Naturelle® HF-E	Environmentally considerate fluid and fire-resistant (MSHA and FM approved)			Contact your Shell representative for details

FULL PRODUCT AND SERVICE PORTFOLIO

Shell Lubricants has been named a global leader in lubricants for 10 years in a row (Kline 2016), and Shell Tellus® hydraulic fluids have offered benefits to users for more than 70 years. Shell is constantly investing to develop better lubrication solutions, including advanced synthetic technologies such as:

- Shell Omala® S4 GXV* synthetic gear oil for long life in demanding applications, Siemens MD approved.
- Shell Corena® S4 R air compressor oil for up to 12,000 hours of protection.

In addition, Shell provides the Shell LubeAnalyst™ oil condition monitoring service, which as part of a preventative maintenance program can help maximize your equipment and lubricant performance.

Whatever your needs or application, Shell can provide a full range of oils and greases, including synthetic, high-performance products and additional services.





Find out more by visiting www.shell.com/tellus

"Shell Lubricants" refers to the various Shell companies engaged in the lubricant business