According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Version 1.5	Revision Date: 08/12/2020	SDS Number: 800001005871	Print Date: 10/28/2020 Date of last issue: 12/31/2015			
SECTION	1. IDENTIFICATION					
Produ	uct name	: Shell Omala	S4 GX 460			
Produ	uct code	: 001D7853	: 001D7853			
Manu	afacturer or supplier	s details				
Manu	facturer/Supplier	: Shell Oil Pro	oducts US			

Manufacturer/Supplier	: Shell Oil Products US
	PO Box 4427
	Houston TX 77210-4427
	USA
SDS Request	: (+1) 877-276-7285
Customer Service	:

Emergency telephone number

Spill Information		877-504-9351
Health Information	:	877-242-7400

Recommended use of the chemical and restrictions on use Recommended use : Gear lubricant.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Based on available data this substance / mixture does not meet the classification criteria.

GHS label elements Hazard pictograms	:	No Hazard Symbol required
Signal word	:	No signal word
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard under GHS criteria. HEALTH HAZARDS: Not classified as a health hazard under GHS criteria. ENVIRONMENTAL HAZARDS: Not classified as an environmental hazard under GHS criteria.
Precautionary statements	:	Prevention: No precautionary phrases. Response: No precautionary phrases. Storage: No precautionary phrases.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Version	Revision Date:
1.5	08/12/2020

SDS Number: 800001005871 Print Date: 10/28/2020 Date of last issue: 12/31/2015

Disposal:

No precautionary phrases.

Other hazards which do not result in classification

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

The classification of this material is based on OSHA HCS 2012 criteria.

Under normal conditions of use or in a foreseeable emergency, this product does not meet the definition of a hazardous chemical when evaluated according to the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture	:	Mixture
---------------------	---	---------

Chemical nature : Blend of polyolefins and additives.

Hazardous components

SECTION 4. FIRST-AID MEASURES				
If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.		
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.		
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.		
If swallowed	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.		
Most important symptoms and effects, both acute and delayed	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.		
Protection of first-aiders	:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.		
Indication of any immediate medical attention and special treatment needed	:	Treat symptomatically.		

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Version	Revision Date:	SDS Number:	Print Date: 10/28/2020
1.5	08/12/2020	800001005871	Date of last issue: 12/31/2015

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	:	Foam, water spray or fog. Dry chemical powder, carbon diox- ide, sand or earth may be used for small fires only.
Unsuitable extinguishing media	:	Do not use water in a jet.
Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.
Specific extinguishing meth- ods	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- tive equipment and emer- gency procedures	:	Avoid contact with skin and eyes.
Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.
		Local authorities should be advised if significant spillages cannot be contained.
Methods and materials for containment and cleaning up	:	Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.
Additional advice	:	For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet. For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7. HANDLING AND STORAGE

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Vers 1.5	ion Revision Date: 08/12/2020		0S Number: 0001005871	Print Date: 10/28/2020 Date of last issue: 12/31/2015
	Technical measures	:	vapours, mists or Use the information sessment of local	e ventilation if there is risk of inhalation of aerosols. on in this data sheet as input to a risk as- circumstances to help determine appropri- fe handling, storage and disposal of this
Advice on safe handling		:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.	
	Avoidance of contact	:	Strong oxidising a	gents.
	Product Transfer	: Proper grounding and bonding procedures should during all bulk transfer operations to avoid static a		
	Further information on stor- age stability		Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.	
			Store at ambient t	emperature.
	Packaging material	:	Suitable material: steel or high dens Unsuitable materi	
	Container Advice	:		ainers should not be exposed to high tem- e of possible risk of distortion.

SECTION 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Components with workplace control parameters

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substanc-

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Version	Revision Date:	SDS Number:	Print Date: 10/28/2020
1.5	08/12/2020	800001005871	Date of last issue: 12/31/2015

es http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

Engineering measures :	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations.
	Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.
	General Information: Define procedures for safe handling and maintenance of controls. Educate and train workers in the hazards and control measures relevant to normal activities associated with this product. Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation. Drain down system prior to equipment break-in or mainte- nance. Retain drain downs in sealed storage pending disposal or subsequent recycle. Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard con- taminated clothing and footwear that cannot be cleaned. Practice good housekeeping.
Personal protective equipment	
Respiratory protection :	No respiratory protection is ordinarily required under normal

Respiratory protection	:	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].
Hand protection Remarks	:	Where hand contact with the product may occur the use of

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Versio 1.5	n Revision Date: 08/12/2020	-	S Number: 0001005871	Print Date: 10/28/2020 Date of last issue: 12/31/2015
			US: F739) made f suitable chemical gloves Suitability a usage, e.g. freque sistance of glove glove suppliers. C Personal hygiene Gloves must only gloves, hands sho cation of a non-pe For continuous co through time of m 480 minutes when short-term/splash recognize that sui may not be availa time maybe accept and replacement a good predictor of dependent on the Glove thickness s	o relevant standards (e.g. Europe: EN374, from the following materials may provide protection. PVC, neoprene or nitrile rubber and durability of a glove is dependent on ency and duration of contact, chemical re- material, dexterity. Always seek advice from contaminated gloves should be replaced. is a key element of effective hand care. be worn on clean hands. After using buld be washed and dried thoroughly. Appli- erfumed moisturizer is recommended. ontact we recommend gloves with break- ore than 240 minutes with preference for > e suitable gloves can be identified. For protection we recommend the same but table gloves offering this level of protection ble and in this case a lower breakthrough otable so long as appropriate maintenance regimes are followed. Glove thickness is not of glove resistance to a chemical as it is exact composition of the glove material. hould be typically greater than 0.35 mm glove make and model.
E	ye protection			led such that it could be splashed into eyes, ar is recommended.
S	kin and body protection		work clothes.	not ordinarily required beyond standard to wear chemical resistant gloves.
Р	rotective measures			e equipment (PPE) should meet recom- standards. Check with PPE suppliers.
Т	hermal hazards	:	Not applicable	
E	nvironmental exposure co	ontro	ls	
G	eneral advice		vant environmenta of the environmer	measures to fulfill the requirements of rele- al protection legislation. Avoid contamination at by following advice given in Section 6. If at undissolved material from being dis-

necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances

must be observed for the discharge of exhaust air containing vapour.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:Liquid at room temperature.Colour:amber

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Vers 1.5	sion	Revision Date: 08/12/2020	-	S Number: 0001005871	Print Date: 10/28/2020 Date of last issue: 12/31/2015
	Odour 1	Threshold	:	Data not availabl	e
	рН		:	Not applicable	
	pour po	int	:	-36 °C / -33 °F Method: ISO 301	6
	Melting	/ freezing point		Data not availabl	e
	Initial bo range	oiling point and boiling	:	> 280 °C / 536 °F estimated value(
	Flash p	oint	:	264 °C / 507 °F	
				Method: ISO 259	2
	Evapora	ation rate	:	Data not availabl	e
	Flamma	ability (solid, gas)	:	Data not availabl	e
		explosion limit / upper bility limit	:	Typical 10 %(V)	
		explosion limit / Lower bility limit	:	Typical 1 %(V)	
	Vapour	pressure	:	< 0.5 Pa (20 °C /	68 °F)
				estimated value(6)
	Relative	e vapour density	:	> 1 estimated value(s	3)
	Relative	e density	:	0.879 (15 °C / 59	°F)
	Density		:	879 kg/m3 (15.0 Method: ISO 121	
	Solubili Wate	ty(ies) er solubility	:	negligible	
	Solu	bility in other solvents	:	Data not availabl	e
	Partition octanol	n coefficient: n- /water	:	log Pow: > 6 (based on inform	ation on similar products)
	Auto-igi	nition temperature	:	> 320 °C / 608 °F	-
		position temperature	:	Data not availabl	e
	Viscosit Visc	ty osity, dynamic	:	Data not availabl	e

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Vers 1.5	sion	Revision Date: 08/12/2020		S Number:)001005871	Print Date: 10/28/2020 Date of last issue: 12/31/2015
	Viso	cosity, kinematic	:	462.5 mm2/s (40 Method: Unspec	
				50 mm2/s (100 °	C / 212 °F)
				Method: Unspec	ified
	Explos	ive properties	:	Not classified	
	Oxidizi	ng properties	:	Data not availab	e
	Conductivity		:	This material is r	not expected to be a static accumulator.
SEC	TION 1	0. STABILITY AND RE	EAC	ΤΙVITY	
	Reactiv	vity	:		s not pose any further reactivity hazards in listed in the following sub-paragraph.
	Chemi	cal stability	:	Stable.	
	Possib tions	ility of hazardous reac-	:	Reacts with stro	ng oxidising agents.

Conditions to avoid	:	Extremes of temperature and direct sunlight.
---------------------	---	--

Incompatible materials	: Strong oxidising agents.
------------------------	----------------------------

Hazardous decomposition	:	No decomposition if stored and applied as directed.
products		

SECTION 11. TOXICOLOGICAL INFORMATION

Basis for assessment	:	Information given is based on data on the components and the toxicology of similar products.Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure

Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:		
Acute oral toxicity	:	LD50 (rat): > 5,000 mg/kg Remarks: Low toxicity: Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Remarks: Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	LD50 (Rabbit): > 5,000 mg/kg Remarks: Low toxicity:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Version	Revision Date:	SDS Number:	Print
1.5	08/12/2020	800001005871	Date

Print Date: 10/28/2020 Date of last issue: 12/31/2015

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: Not a skin sensitiser. Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
ΝΤΡ	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
Reproductive toxicity	

Product:

:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Version	Revision Date:	SDS Number:	Print Date: 10/28/2020
1.5	08/12/2020	800001005871	Date of last issue: 12/31/2015

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

SECTION 12. ECOLOGICAL INFORMATION

Basis for assessment	 Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products. Unless indicated otherwise, the data presented is representa- tive of the product as a whole, rather than for individual com- ponent(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).
Ecotoxicity	
<u>Product:</u> Toxicity to fish (Acute toxici- : ty)	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic: Based on available data, the classification criteria are not met.
Toxicity to daphnia and other : aquatic invertebrates (Acute toxicity)	Remarks: LL/EL/IL50 > 100 mg/l Practically non toxic:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Version 1.5	Revision Date: 08/12/2020		0S Number: 0001005871	Print Date: 10/28/2020 Date of last issue: 12/31/2015
			Based on availabl	e data, the classification criteria are not met.
	Toxicity to algae (Acute tox- icity)		Remarks: LL/EL/II Practically non to Based on availabl	
Toxi icity)	icity to fish (Chronic tox-)	:	Remarks: Data not available	
aqua	Toxicity to daphnia and other aquatic invertebrates (Chron- ic toxicity)		Remarks: Data no	ot available
	icity to microorganisms ute toxicity)	:	Remarks: Data no	ot available
Pers	sistence and degradabili	ity		
	<u>duct:</u> legradability	:	Major constituents	dily biodegradable. s are inherently biodegradable, but contains may persist in the environment.
Bioa	accumulative potential			
	<u>duct:</u> accumulation	:	Remarks: Contain cumulate.	as components with the potential to bioac-
Mob	pility in soil			
<u>Proe</u> Mob	<u>duct:</u> vility	:	If it enters soil, it v mobile.	under most environmental conditions. vill adsorb to soil particles and will not be
			Remarks: Floats of	on water.
	er adverse effects			
	<u>duct:</u> itional ecological infor- ion	:	ozone creation po Product is a mixtu	one depletion potential, photochemical otential or global warming potential. Ire of non-volatile components, which will not in any significant quantities under normal
			Poorly soluble mix Causes physical f	xture. ouling of aquatic organisms.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Version	Revision Date:	SDS Number:	Print Date: 10/28/2020
1.5	08/12/2020	800001005871	Date of last issue: 12/31/2015

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues :	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal meth- ods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.
Contaminated packaging :	Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.
Local legislation Remarks	: Disposal should be in accordance with applicable regional, national, and local laws and regulations.

SECTION 14. TRANSPORT INFORMATION

National Regulations

US Department of Transportation Classification (49 CFR Parts 171-180)

Not regulated as a dangerous good

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

Special precautions for user

Remarks

: Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Version	Revision Date:	SDS Number:
1.5	08/12/2020	800001005871

Print Date: 10/28/2020 Date of last issue: 12/31/2015

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

*: This material does not contain any components with a CERCLA RQ., Shell classifies this material as an "oil" under the CERCLA Petroleum Exclusion, therefore releases to the environment are not reportable under CERCLA.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards	No SARA Hazards	
SARA 313	This material does not contain any chemical components known CAS numbers that exceed the threshold (De Minin reporting levels established by SARA Title III, Section 313	nis)

Clean Water Act

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

US State Regulations

Pennsylvania Right To Know

Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7
Distillates (petroleum), hydrotreated light	64742-47-8

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

The components of this product are reported in the following inventories:

EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.
DSL	:	All components listed.

SECTION 16. OTHER INFORMATION

Further information

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Version	Revision Date:	SDS Number:	Print
1.5	08/12/2020	800001005871	Date

Print Date: 10/28/2020 Date of last issue: 12/31/2015

NFPA Rating (Health, Fire, Reac- 0, 1, 0 tivity)

Full text of other abbreviations

Abbreviations and Acronyms :	The standard abbreviations and acronyms used in this docu- ment can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.
	ACGIH = American Conference of Governmental Industrial
	Hygienists ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road
	AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials
	BEL = Biological exposure limits
	BTEX = Benzene, Toluene, Ethylbenzene, Xylenes CAS = Chemical Abstracts Service
	CEFIC = European Chemical Industry Council
	CLP = Classification Packaging and Labelling COC = Cleveland Open-Cup
	DIN = Deutsches Institut fur Normung
	DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level
	DSL = Canada Domestic Substance List
	EC = European Commission
	EC50 = Effective Concentration fifty ECETOC = European Center on Ecotoxicology and Toxicolo-
	gy Of Chemicals
	ECHA = European Chemicals Agency
	EINECS = The European Inventory of Existing Commercial Chemical Substances
	EL50 = Effective Loading fifty
	ENCS = Japanese Existing and New Chemical Substances Inventory
	EWC = European Waste Code
	GHS = Globally Harmonised System of Classification and
	Labelling of Chemicals IARC = International Agency for Research on Cancer
	IATA = International Air Transport Association
	IC50 = Inhibitory Concentration fifty IL50 = Inhibitory Level fifty
	IMDG = International Maritime Dangerous Goods
	INV = Chinese Chemicals Inventory
	IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables
	KECI = Korea Existing Chemicals Inventory
	LC50 = Lethal Concentration fifty
	LD50 = Lethal Dose fifty per cent. LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading
	LL50 = Lethal Loading fifty
	MARPOL = International Convention for the Prevention of Pollution From Ships
	NOEC/NOEL = No Observed Effect Concentration / No Ob-
	served Effect Level

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Shell Omala S4 GX 460

Versi 1.5	on Revision Date: 08/12/2020	SDS Number: 800001005871	Print Date: 10/28/2020 Date of last issue: 12/31/2015
		PBT = Persistent PICCS = Philippi Substances PNEC = Predicte REACH = Regist Chemicals RID = Regulation gerous Goods by SKIN_DES = Ski STEL = Short ter TRA = Targeted TSCA = US Toxic TWA = Time-We	n Designation m exposure limit Risk Assessment c Substances Control Act
ļ	A vertical bar () in the left ma	rgin indicates an amer	ndment from the previous version.
C	Sources of key data used to compile the Safety Data Sheet	sources of inform	are from, but not limited to, one or more ation (e.g. toxicological data from Shell material suppliers' data, CONCAWE, EU

Revision Date : 08/12/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

IUCLID date base, EC 1272 regulation, etc).

US / EN